

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Version 2 Revision Date 12.12.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Hexane
Product Number : PRD5435
Brand : Better Equipped
Index-No. : 601-037-00-0
REACH No. : 01-2119480412-44-XXXX
CAS-No. : 110-54-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances
Uses advised against : Not for sale to the general public

1.3 Details of the supplier of the safety data sheet

Company : Better Equipped,
Wrenbury Business Park,
Wrenbury Road,
Wrenbury,
Nantwich, Cheshire,
CW5 8EB, UK
Telephone +44 (0) 800 9707142
Fax +44 (0) 800 066 4443
E-mail address sales@betterequipped.co.uk

1.4 Emergency telephone number

Emergency Phone # +44 (0)1270 781238

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225
Skin irritation (Category 2), H315
Reproductive toxicity (Category 2), H361f
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336
Specific target organ toxicity - repeated exposure (Category 2), H373
Aspiration hazard (Category 1), H304
Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P370 + P378	In case of fire: Use dry powder or dry sand to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
Supplemental Hazard Statements	none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms	:	<i>n</i> -Hexane
Formula	:	C ₆ H ₁₄
Molecular weight	:	86.18 g/mol
CAS-No.	:	110-54-3
EC-No.	:	203-777-6
Index-No.	:	601-037-00-0
Registration number	:	01-2119480412-44-XXXX

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
n-Hexane		
CAS-No.	110-54-3	Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Chronic 2; H225, H315, H361f, H336, H373, H304, H411 Concentration limits: >= 5 %: STOT RE 2, H373; >= 20 %: STOT SE 3, H336;
EC-No.	203-777-6	
Index-No.	601-037-00-0	
Registration number	01-2119480412-44-XXXX	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Remove contaminated clothing. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****- 6.1.1 For non-emergency personnel**

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- 6.1.2 For emergency responders

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage
7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.
Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

7.1.2 Advice on general occupational hygiene:

- No smoking.
- Do not eat or drink.
- Wash hands after use.
- Remove contaminated clothing.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection
8.1 Control parameters
Components with workplace control parameters

Component	CAS-No.	ValueForm of exposure	Control parameters	Basis
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m ³	Europe. Indicative occupational exposure limit values
	Remarks	Indicative		
		TWA	20 ppm 72 mg/m ³	UK. EH40 WEL - Workplace Exposure Limits
		Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used		

8.1.2 Information on currently recommended monitoring procedures

For currently recommended monitoring procedures, see HSE series 'Methods for the Determination of Hazardous Substances' (MDHS)

8.1.3 The relevant DNELs and PNECs for the substance/s for the exposure scenarios:

DNEL's. The derived no- or minimum effect level (DN(M)EL) is the level of exposure above which a human should not be exposed to a substance. Please note that when more than one summary is provided, DN(M)EL values may refer to constituents of the substance and not to the substance as a whole.

Data for WORKERS

INHALATION Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 75 mg/m ³	neurotoxicity
Acute /short term:	-	-
Local Effects		
Long-term:	-	-
Acute /short term:	-	-
DERMAL Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 11 mg/kg bw/day	neurotoxicity
Acute /short term:	-	-
Local Effects		
Long-term:	-	-
Acute /short term:	-	-
EYE Exposure		
-		

Data for the GENERAL POPULATION

INHALATION Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 16 mg/m ³	neurotoxicity
Acute /short term:	-	-
Local Effects		
Long-term:	-	-
Acute /short term:	-	-

DERMAL Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 5.3 mg/kg bw/day	neurotoxicity
Acute /short term:	-	-
Local Effects		
Long-term:	-	-
Acute /short term:	-	-
ORAL Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 4 mg/kg bw/day	neurotoxicity
Acute /short term:	-	-
EYE Exposure		
-		

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Use Local exhaust ventilation (LEV).

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 59 min

Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

a) Appearance	Form: liquid Colour: colourless
b) Odour	No data available
c) Odour Threshold	No data available
d) pH	7.0
e) Melting point/freezing point	Melting point/range: -95 °C
f) Initial boiling point and boiling range	69 °C
g) Flash point	-26.0 °C - closed cup
h) Evaporation rate	15.8
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 7.7 %(V) Lower explosion limit: 1.2 %(V)
k) Vapour pressure	341.3 hPa at 37.7 °C 176.0 hPa at 20.0 °C
l) Vapour density	No data available
m) Relative density	0.659 g/mL at 25 °C
n) Water solubility	insoluble
o) Partition coefficient: n-octanol/water	log Pow: 3.90 - 4.11
p) Auto-ignition temperature	234.0 °C
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

None based on the data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.3 Conditions to avoid

Heat, flames and sparks.

10.4 Incompatible materials

Oxidizing agents

10.5 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

LD50 Oral - Rat - male and female - 16,000 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - 4 h - 172 mg/l

Remarks: (RTECS)

LD50 Dermal - Rabbit - > 2,000 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

The liquid is mildly irritating to the skin. Repeated or prolonged contact may defat the skin producing irritation and dermatitis.

Serious eye damage/eye irritation

Both the vapour and liquid will, act as an eye irritant.

Respiratory or skin sensitisation

Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes and respiratory tract. High concentrations of vapour may cause narcosis. Symptoms include drowsiness, mental confusion and unconsciousness. Chronic exposure can lead to loss of sensation in hands and feet and has been linked with neurotoxic effects, progressing for several months following exposure, followed by slow recovery.

Germ cell mutagenicity

In vitro mammalian cell gene mutation test

Mouse lymphoma test

Result: Positive results were obtained in some in vitro tests.

Ames test

Salmonella typhimurium

Result: negative

(National Toxicology Program)

Carcinogenicity

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

Suspected of damaging the unborn child.

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure. - Nervous system

Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary oedema and pneumonitis.

Additional Information

RTECS: MN9275000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish

LC50 - Pimephales promelas (fathead minnow) - 2.5 mg/l - 96 h Remarks: (ECOTOX Database)

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 2.1 mg/l - 48 h Remarks: (Lit.)

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations
13.1 Waste treatment methods
Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Unused product may be returned and reused, in addition to disposal.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information
14.1 UN number

ADR/RID: 1208

IMDG: 1208

IATA: 1208

14.2 UN proper shipping name

ADR/RID: HEXANES

IMDG: HEXANES

IATA: Hexanes

14.3 Transport hazard class(es)

ADR/RID: 3

IMDG: 3

IATA: 3

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: yes

IMDG Marine pollutant: yes

IATA: no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N/A

SECTION 15: Regulatory information
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information
Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.



Revisions made since previous version of data sheet:

The following sections of this data sheet have been updated:

1.2, 4.1, 5.1, 5.2, 6.1, 7.1, 8.1, 10.3, 11.1, 12.2, 12.3, 12.4, 13.1, 14.7, 15.1, 16

We strongly recommend reading the entire data sheet for this chemical in preparation ahead of use.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Better Equipped and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.
