according to Regulation (EC) No. 1907/2006 Version 2 Revision Date 10.12.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Styrene

Product Number : 5463

Brand : Better Equipped Index-No. : 601-026-00-0

REACH No. : A registration number is not available for this substance as the substance

or its uses are exempted from registration or the annual tonnage does

not require a registration.

CAS-No. : 100-42-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

Uses advised against : Not for sale to the general public

1.3 Details of the supplier of the safety data sheet

Company : Better Equipped,

Wrenbury Business Park,

Wrenbury Road,

Wrenbury,

Nantwich, Cheshire, CW5 8EB, UK

Telephone +44 (0) 800 9707142 Fax +44 (0) 800 066 4443

E-mail address sales@betterequipped.co.uk

1.4 Emergency telephone number

Emergency Phone # +44 (0)1270 781238

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 3), H226

Acute toxicity, Inhalation (Category 4), H332

Skin irritation (Category 2), H315 Eye irritation (Category 2), H319

Reproductive toxicity (Category 2), H361d

Specific target organ toxicity - repeated exposure (Category 1), H372

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word Danger

Hazard statement(s)

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P280 Wear protective gloves/ protective clothing/ eye protection/ face

protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P370 + P378 In case of fire: Use dry powder or dry sand to extinguish.

Supplemental Hazard

Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. Lachrymator.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : C8H8

 Molecular weight
 : 104.15 g/mol

 CAS-No.
 : 100-42-5

 EC-No.
 : 202-851-5

 Index-No.
 : 601-026-00-0

Hazardous ingredients according to Regulation (EC) No 1272/2008

	no according to mogalane	(=0) :=:=;=000	
Component		Classification	Concentration
Styrene			
CAS-No.	100-42-5	Flam. Liq. 3; Acute Tox. 4;	<= 100 %
EC-No.	202-851-5	Skin Irrit. 2; Eye Irrit. 2; Repr.	
Index-No.	601-026-00-0	2; STOT RE 1; H226, H332,	
		H315, H319, H361d, H372	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.



If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Container explosion may occur under fire conditions., Vapours may form explosive mixture with air.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- 6.1.1 For non-emergency personnel

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

- 6.1.2 For emergency responders

Wear respiratory protection. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

7.1.2 Advice on general occupational hygiene:

- No smoking.
- Do not eat or drink.
- Wash hands after use.
- Remove contaminated clothing.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in cool place.

Recommended storage temperature 2 - 8 °C

Light sensitive.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	ValueForm	Control	Basis
		of exposure	parameters	
Styrene	100-42-5	TWA	100 ppm	UK. EH40 WEL - Workplace
			430 mg/m3	Exposure Limits
		STEL	250 ppm	UK. EH40 WEL - Workplace
			1,080 mg/m3	Exposure Limits

8.1.2 Information on currently recommended monitoring procedures

For currently recommended monitoring procedures, see HSE series 'Methods for the Determination of Hazardous Substances' (MDHS).

8.1.3 The relevant DNELs and PNECs for the substance/s for the exposure scenarios:

DNEL's. The derived no- or minimum effect level (DN(M)EL) is the level of exposure above which a human should not be exposed to a substance. Please note that when more than one summary is provided, DN(M)EL values may refer to constituents of the substance and not to the substance as a whole.

Data for Workers

INHALATION Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 85 mg/m ³	repeated dose toxicity
Acute /short term:	(DNEL) 100 mg/m ³	neurotoxicity



Local Effects		
Long-term:	(DNEL) 100 mg/m³	irritation (respiratory tract)
Acute /short term:	(DNEL) 100 mg/m³	irritation (respiratory tract)
DERMAL Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 406 mg/kg bw/day	repeated dose toxicity
Acute /short term:	Low hazard (no threshold derived)	
Local Effects		
Long-term:	Low hazard (no threshold derived)	
Acute /short term:	Low hazard (no threshold derived)	
EYE Exposure		
Low hazard (no threshold derived)		

Data for the General Population

INHALATION Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 1 mg/m³	repeated dose toxicity
Acute /short term:	(DNEL) 10 mg/m ³	repeated dose toxicity
Local Effects		
Long-term:	(DNEL) 1 mg/m³	repeated dose toxicity
Acute /short term:	(DNEL) 10 mg/m³	repeated dose toxicity
DERMAL Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 343 mg/kg bw/day	repeated dose



		toxicity
Acute /short term:	Low hazard (no threshold derived)	
Local Effects		
Long-term:	Low hazard (no threshold derived)	
Acute /short term:	Low hazard (no threshold derived)	
ORAL Exposure	Threshold	Most sensitive study
Systemic Effects		
Long-term:	(DNEL) 7.7 μg/kg bw/day	repeated dose toxicity
Acute /short term:	Low hazard (no threshold derived)	
EYE Exposure		
Low hazard (no threshold derived)		

PNEC's. The Predicted No-Effect Concentration (PNEC) value is the concentration of a substance below which adverse effects in the environment are not expected to occur. Please note that when more than one summary is provided, PNEC values may refer to constituents of the substance and not to the substance as a whole.

Hazard for Aquatic Organisms		
Freshwater	28 - 40 μg/L (2)	
Intermittent releases (freshwater)	40 μg/L (1)	
Marine water	14 - 40 μg/L (2)	
Intermittent releases (marine water)	-	
Sewage treatment plant (STP)	5 mg/L (1)	
Sediment (freshwater)	418 - 614 μg/kg sediment dw (2)	
Sediment (marine water)	307 - 418 μg/kg sediment dw (2)	

Hazard for Air	
Air	No hazard identified (1)
Hazard for Terrestrial Organism	



Soil 146 - 200 μg/kg soil dw (2)	
Hazard for Predators	
Secondary poisoning	No potential for bioaccumulation (1)

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Use Local exhaust ventilation (LEV).

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: >

480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Splash contact Material:

Nitrile rubber

Minimum layer thickness: 0.4 mm Break

through time: 32 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

 $data\ source:\ KCL\ GmbH,\ D\text{-}36124\ Eichenzell,\ phone\ +49\ (0)6659\ 87300,\ e\text{-}mail\ sales @kcl.de,\ test$

method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.



SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Form: liquid, clear a) **Appearance** Colour: colourless b) sweet

Odour

c) Odour Threshold No data available рΗ d) No data available

Melting point/freezing point Melting point/range: -31 °C - lit. e)

f) Initial boiling point and boiling range 145 - 146 °C - lit. Flash point 32.0 °C - closed cup g) Evaporation rate No data available h) Flammability (solid, gas) No data available i)

Upper/lower flammability or explosive limits Upper explosion limit: 8.9 %(V) Lower explosion j)

No data available

No data available

No data available

limit: 1.1 %(V) Vapour pressure 6 hPa at 20 °C

Vapour density 3.6

Relative density 0.906 g/cm3 at 25 °C m)

n) Water solubility 0.05 g/l at 25 °C - slightly soluble Partition coefficient: n- octanol/water No data available o)

Auto-ignition temperature 490.0 °C p)

480.0 °C No data available Decomposition temperature

q) Viscosity r)

Explosive properties s) Oxidizing properties t)

Other safety information 9.2

> Relative vapour density 3.6

SECTION 10: Stability and reactivity

10.1 Reactivity

k)

I)

None based on the data available

10.2 Chemical stability

Stable under recommended storage conditions.

Contains the following stabiliser(s):

4-tert-Butylpyrocatechol (>=30 - <=50 ppm)

10.3 Possibility of hazardous reactions

None under normal processing

Conditions to avoid

May polymerize on exposure to light.

Heat, flames and sparks.

10.5 Incompatible materials

Oxidizing agents, Copper

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - > 6,000 mg/kg



LC50 Inhalation - Rat - 4 h - 12,000 mg/m3

LD50 Dermal - Rat - male and female - > 2,000 mg/kg

Skin corrosion/irritation

Skin - Rabbit

Result: Skin irritation

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 24 h

Respiratory or skin sensitisation

Maximisation Test - Guinea pig

Does not cause skin sensitisation.

(OECD Test Guideline 406)

Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects.

Carcinogenicity

This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Styrene)

Reproductive toxicity

Suspected of damaging the unborn child. Suspected human reproductive toxicant

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

No data available

Additional Information

RTECS: WL3675000

Dermatitis, Central nervous system depression, Nausea, Dizziness, Headache, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Endocrine system. -

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish NOEC - Pimephales promelas (fathead minnow) - 4 mg/l - 96 h

LC50 - Pimephales promelas (fathead minnow) - 32 mg/l - 96 h LOEC - Pimephales promelas (fathead minnow) - 7.6 mg/l - 96 h

Toxicity to daphnia and

other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 4.7 mg/l - 48 h

(OECD Test Guideline 202)



Toxicity to algae IC50 - Pseudokirchneriella subcapitata (green algae) - 1.4 mg/l - 72 h

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: > 60 % - Readily biodegradable.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Toxic to aquatic life.

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. Unused product may be returned and reused, in addition to disposal.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 2055 IMDG: 2055 IATA: 2055

14.2 UN proper shipping name

ADR/RID: STYRENE MONOMER, STABILIZED IMDG: STYRENE MONOMER, STABILIZED

IATA: Styrene monomer, stabilized

14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: III IMDG: III IATA: III

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N/A

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out



SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

Revisions made since previous version of data sheet:

The following sections of this data sheet have been updated:

1.1, 1.2, 4.1, 5.1, 6.1, 7.1, 8.1, 8.2, 11, 12, 13, 14.7, 16

We strongly recommend reading the entire data sheet for this chemical in preparation ahead of use.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Better Equipped and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.