

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 Version 2 Revision Date 13.12.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Universal Indicator Full range
Product Number : 5552
Brand : Better Equipped
Index-No. : 603-002-00-5
REACH No. : 01-2119457610-43-XXXX
CAS-No. : 64-17-5

This substance is a mixture and the hazardous components information have been used for this section.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances
Uses advised against : Not for sale to the general public

1.3 Details of the supplier of the safety data sheet

Company : Better Equipped,
Wrenbury Business Park,
Wrenbury Road,
Wrenbury,
Nantwich, Cheshire,
CW5 8EB, UK
Telephone +44 (0) 800 9707142
Fax +44 (0) 800 066 4443
E-mail address sales@betterequipped.co.uk

1.4 Emergency telephone number

Emergency Phone # +44 (0)1270 781238

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225
Eye irritation (Category 2), H319
Spec target organ tox - single, (category 2), (STOT SE 2).

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other

P305 + P351 + P338 ignition sources. No smoking.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370 + P378 In case of fire: Use dry powder or dry sand to extinguish.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 Supplemental Hazard Statements none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Ethyl alcohol
 Formula : C₂H₆O
 Molecular weight : 46.07 g/mol
 CAS-No. : 64-17-5
 EC-No. : 200-578-6
 Index-No. : 603-002-00-5
 Registration number : 01-2119457610-43-XXXX

Hazardous ingredients according to Regulation (EC) No 1272/2008

| Component | Classification | Concentration |
|---|--|---------------|
| Ethanol | | |
| CAS-No. 64-17-5 | Flam. Liq. 2; Eye Irrit. 2; H225, H319 | >50%≤ 100 % |
| EC-No. 200-578-6 | Concentration limits: | |
| Index-No. 603-002-00-5 | >= 50 %: Eye Irrit. 2A, H319; | |
| Registration number 01-2119457610-43-XXXX | | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Remove contaminated clothing. Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- 6.1.1 For non-emergency personnel

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

- 6.1.2 For emergency responders

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

7.1.2 Advice on general occupational hygiene:

- No smoking.
- Do not eat or drink.
- Wash hands after use.
- Remove contaminated clothing.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

| Component | CAS-No. | ValueForm of exposure | Control parameters | Basis |
|-----------|---------|---|--------------------------------------|--|
| Ethanol | 64-17-5 | TWA | 1,000 ppm 1,920 mg/m ³ | UK. EH40 WEL - Workplace Exposure Limits |
| | Remarks | Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used | | |

8.1.2 Information on currently recommended monitoring procedures

For currently recommended monitoring procedures, see HSE series 'Methods for the Determination of Hazardous Substances' (MDHS)

8.1.3 The relevant DNELs and PNECs for the substance/s for the exposure scenarios:

DNEL's. The derived no- or minimum effect level (DN(M)EL) is the level of exposure above which a human should not be exposed to a substance. Please note that when more than one summary is provided, DN(M)EL values may refer to constituents of the substance and not to the substance as a whole.

Derived No Effect Level (DNEL)

| Application Area | Exposure routes | Health effect | Value |
|------------------|-----------------|----------------------------|------------------------|
| Workers | Inhalation | Long-term systemic effects | 950 mg/m ³ |
| Workers | Skin contact | Long-term systemic effects | 343mg/kg BW/d |
| Workers | Ingestion | Long-term systemic effects | 343mg/kg BW/d |
| Workers | Inhalation | Acute local effects | 1900 mg/m ³ |

PNEC's. The Predicted No-Effect Concentration (PNEC) value is the concentration of a substance below which adverse effects in the environment are not expected to occur. Please note that when more than one summary is provided, PNEC values may refer to constituents of the substance and not to the substance as a whole.

Predicted No Effect Concentration (PNEC)

| Compartment | Value |
|------------------------|------------|
| Soil | 0.63 mg/kg |
| Marine water | 0.79 mg/l |
| Fresh water | 0.96 mg/l |
| Fresh water sediment | 3.6 mg/l |
| Sewage treatment plant | 580 mg/l |

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. Use Local exhaust ventilation (LEV).

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.3 mm

Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M)

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.2 mm

Break through time: 38 min

Material tested: Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Impervious clothing, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|---|
| a) Appearance | Form: liquid, Colour: Green |
| b) Odour | Ethanol like |
| c) Odour Threshold | No data available |
| d) pH | pH 6-8 at 20 °C |
| e) Melting point/freezing point | Melting point/range: -114 °C |
| f) Initial boiling point and boiling range | 78 °C |
| g) Flash point | 23 °C - closed cup |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 19 %(V) Lower explosion limit: 3.3 %(V) |
| k) Vapour pressure | 59.5 hPa at 20.0 °C |
| l) Vapour density | No data available |
| m) Relative density | 0.789 g/mL at 25 °C |
| n) Water solubility | completely soluble |
| o) Partition coefficient: n-octanol/water | No data available |
| p) Auto-ignition temperature | No data available |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |
| t) Oxidizing properties | No data available |

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

None known based on the data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Alkali metals, Oxidizing agents, Peroxides

10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

LD50 Oral - Rat - male and female - 10,470 mg/kg
(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124.7 mg/l
(OECD Test Guideline 403)

LC50 Inhalation - Rat - 4 h - 30,000 mg/l

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

Respiratory or skin sensitisation

Sensitisation test:

Result: negative

Remarks: (IUCLID)

Germ cell mutagenicity

Ames test

Salmonella typhimurium

Result: negative

In vitro mammalian cell gene mutation test

Mouse lymphoma test

Result: negative

OECD Test Guideline 478

Mouse - male

Carcinogenicity

Carcinogenicity - Mouse - Oral

Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkin's disease.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

Reproductive toxicity - Human - female - Oral

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects.

Effects on Newborn: Drug dependence.

Aspiration hazard

No data available

Additional Information

RTECS: KQ6300000

irritant effects, respiratory paralysis, Dizziness, narcosis, inebriation, euphoria, Nausea, Vomiting

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead minnow) - 15.3 mg/l - 96 h

Toxicity to daphnia and other aquatic invertebrates LC50 - Ceriodaphnia dubia (water flea) - 5,012 mg/l - 48 h

NOEC - Daphnia magna (Water flea) - 9.6 mg/l - 9 d

Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 275 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradabilityBiodegradability aerobic - Exposure time 15 d
Result: 95 % - Readily biodegradable.
(OECD Test Guideline 301E)**12.3 Bioaccumulative potential**

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Unused product may be returned and reused, in addition to disposal.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information**14.1 UN number**

ADR/RID: 1170

IMDG: 1170

IATA: 1170

14.2 UN proper shipping name

ADR/RID: ETHANOL MIXTURE

MIMDG: ETHANOL MIXTURE

IATA: Ethanol Mixture

| | | |
|---|---------------------------|-----------|
| 14.3 Transport hazard class(es) ADR/RID: 3 | IMDG: 3 | IATA: 3 |
| 14.4 Packaging group ADR/RID: III | IMDG: III | IATA: III |
| 14.5 Environmental hazards ADR/RID: no | IMDG Marine pollutant: no | IATA: no |
| 14.6 Special precautions for user No data available | | |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code N/A | | |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.
- 15.2 Chemical safety assessment**
A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

| | |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |

Revisions made since previous version of data sheet:

The following sections of this data sheet have been updated:

1.1, 1.2, 2.2, 4.1, 5.1, 6.1, 7.1, 8.1, 8.2, 9.1, 10.3, 11.1, 13.1, 14.2, 14.7, 15.1, 16

We strongly recommend reading the entire data sheet for this chemical in preparation ahead of use.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Better Equipped and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product.

Annex: Exposure scenario

Identified uses:

Use: Used as chemical intermediate

| |
|---|
| SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites |
| SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals |
| PC19: Intermediate |
| PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities |
| ERC1, ERC4, ERC6a: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates) |

Use: Formulation of preparations

| |
|--|
| SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites |
| SU 10, SU 3: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys), Industrial uses: Uses of substances as such or in preparations at industrial sites |
| PROC3: Use in closed batch process (synthesis or formulation) PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) |
| ERC2: Formulation of preparations |

Use: Industrial use of processing aids in processes and products, not becoming part of articles

| |
|---|
| SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites |
| SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals |
| PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities |
| ERC1, ERC4, ERC6a: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in manufacture of another substance (use of intermediates) |

Use: Used as laboratory reagent

| |
|--|
| SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| SU 3, SU 22: Industrial uses: Uses of substances as such or in preparations at industrial sites, Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| PC21: Laboratory chemicals |
| PROC15: Use as laboratory reagent |
| ERC2, ERC4, ERC8a: Formulation of preparations, Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems |

Use: Surface treatment

| |
|---|
| SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites |
|---|

| |
|---|
| SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites |
| PROC10: Roller application or brushing |
| PROC13: Treatment of articles by dipping and pouring |
| ERC4: Industrial use of processing aids in processes and products, not becoming part of articles |

1. Short title of Exposure Scenario: Used as chemical intermediate

| | |
|----------------------------------|--------------------------------------|
| Main User Groups | : SU 3 |
| Sectors of end-use | : SU 3, SU9 |
| Chemical product category | : PC19 |
| Process categories | : PROC1, PROC2, PROC3, PROC4, PROC8b |
| Environmental Release Categories | : ERC1, ERC4, ERC6a: |

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b, PC19

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 240 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|-----------------------------------|------------|-----------------------------|-------|
| PROC1 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 0.3429 mg/kg BW/d | 0.001 |
| PROC1 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 0.0192083 mg/m ³ | 0 |
| PROC2 | ECETOC TRA | Without Local | Inhalation | 19.2083333 | 0.02 |

| | | Exhaust Ventilation | | mg/m ³ | |
|--------|------------|-----------------------------------|------------|------------------------------|-------|
| PROC2 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 1.3714 mg/kg BW/d | 0.004 |
| PROC3 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 0.3429 mg/kg BW/d | 0.001 |
| PROC3 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 48.0208333 mg/m ³ | 0.051 |
| PROC4 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 38.4166667 mg/m ³ | 0.04 |
| PROC4 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 6.8571 mg/kg BW/d | 0.02 |
| PROC8b | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 6.8571 mg/kg BW/d | 0.02 |
| PROC8b | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Formulation of preparations

Main User Groups : SU 3
 Sectors of end-use : SU 10, SU 3
 Process categories : PROC3, PROC5, PROC8a, PROC8b, PROC9
 Environmental Release Categories : ERC2:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC3, PROC5, PROC8a, PROC8b, PROC9

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 240 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|-----------------------------------|------------|------------------------------|-------|
| PROC3 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 48.0208333 mg/m ³ | 0.051 |
| PROC3 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 0.3429 mg/kg BW/d | 0.001 |
| PROC5 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 13.7143 mg/kg BW/d | 0.04 |
| PROC5 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |
| PROC8a | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 13.7143 mg/kg BW/d | 0.04 |
| PROC8a | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |
| PROC8b | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |
| PROC8b | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 6.8571 mg/kg BW/d | 0.02 |
| PROC9 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 6.8571 mg/kg BW/d | 0.02 |
| PROC9 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Industrial use of processing aids in processes and products, not becoming part of articles

Main User Groups : SU 3
 Sectors of end-use : SU 3, SU9
 Process categories : PROC1, PROC2, PROC3, PROC4, PROC8b
 Environmental Release Categories : ERC1, ERC4, ERC6a:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC1, ERC4, ERC6a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PROC8b

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 240 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|-----------------------------------|------------|------------------------------|-------|
| PROC1 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 0.3429 mg/kg BW/d | 0.001 |
| PROC1 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 0.0192083 mg/m ³ | 0 |
| PROC2 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 19.2083333 mg/m ³ | 0.02 |
| PROC2 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 1.3714 mg/kg BW/d | 0.004 |

| | | | | | |
|--------|------------|-----------------------------------|------------|------------------------------|-------|
| PROC3 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 0.3429 mg/kg BW/d | 0.001 |
| PROC3 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 48.0208333 mg/m ³ | 0.051 |
| PROC4 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 6.8571 mg/kg BW/d | 0.02 |
| PROC4 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 38.4166667 mg/m ³ | 0.04 |
| PROC8b | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |
| PROC8b | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 6.8571 mg/kg BW/d | 0.02 |

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Used as laboratory reagent

Main User Groups : SU 22
 Sectors of end-use : SU 3, SU 22
 Chemical product category : PC21
 Process categories : PROC15
 Environmental Release Categories : ERC2, ERC4, ERC8a:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2, ERC4, ERC8a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC15, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : 1 - 4 h

Frequency of use : 240 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|-----------------------------------|------------|------------------------------|-------|
| PROC15 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 19.2083333 mg/m ³ | 0.02 |
| PROC15 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 0.3429 mg/kg BW/d | 0.001 |

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Surface treatment

Main User Groups : **SU 3**
 Sectors of end-use : **SU 3**
 Process categories : **PROC10, PROC13**
 Environmental Release Categories : **ERC4:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC10, PROC13

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
 Physical Form (at time of use) : Liquid substance

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 240 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organisational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection and gloves., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

| Contributing Scenario | Exposure Assessment Method | Specific conditions | Value | Level of Exposure | RCR* |
|-----------------------|----------------------------|-----------------------------------|------------|------------------------------|-------|
| PROC10 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |
| PROC10 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 27.4286 mg/kg BW/d | 0.08 |
| PROC13 | ECETOC TRA | Without Local Exhaust Ventilation | Dermal | 13.7143 mg/kg BW/d | 0.04 |
| PROC13 | ECETOC TRA | Without Local Exhaust Ventilation | Inhalation | 96.0416667 mg/m ³ | 0.101 |

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).